



Two-Roller Gluing Machine with standard 3 m conveyor belt is equipped with a top-side gluing system. The basic model is designed for gluing flexible thin materials and an additional pressure roller device for processing of paperboard, cardboard, PVC, wood etc. up to a thickness of 15 mm. The conveyor is equipped with own adjustable motor. Conveyor belt can be stopped by pedal in any position without stopping the Gluing Machine.

Action: The products to be glued are fed manually from a feed table into the gluing device. After being glued, the item is delivered automatically onto the conveyor belt. A further rational treatment of the glued product is possible from both sides of the belt.

Motor : Motor for 230 volts AC 50 cy 1 ph or 380 volts , other currents/voltages on request. Variable speed control.

Working size: 500 mm, 650 mm, 800 mm, 1000 mm, 1200 mm

Options : Hot-glue attachment, table model available, recirculation pump system, vaccum conveyor, rollers and glue tray in stainless steel



Gluing Machine Mod. Senator as table machine 500 mm working size



Vaccum conveyor for Gluing Machine Mod. Senator



Gluing Machine Mod. Senator with hot glue attachment and glue circulation system



SUMBEL GMBH

D-28197 Bremen - Carl-Stockhinger-Str. 5 - Deutschland
Telf. ++49 (421) 544078 - Fax ++49 (421) 544071
Homepage: <http://www.sumbel.de> - E-Mail: info@sumbel.de